



**PRODUCT INFORMATION**

**PRODUCT: DRY GRAPHITE SPRAY**

**PART NO.: BGS1**

**FUNCTION AND APPLICATION:** Use as a lubricant and parting compound on engines, pumps, business machines, etc, wherever heat and friction are a problem.

**OUTSTANDING PROPERTIES:** Contains no oils or moisture-based diluents: is inert to water, oils and alkalis. Effective from -37°C to +537°C.

**USE DIRECTIONS:** Shake well before using. Spray liberally on dry, clean surface. Repeat if necessary. Turn can upside down and spray to clear nozzle.

**PRECAUTIONS:** View MSDS at [www.gunk.ca](http://www.gunk.ca)

**STORAGE & HANDLING:** Do not place in hot water, near radiators or stoves, or any other source of heat. Do not puncture or incinerate can. Store below 50°C. Do not use in presence of open flame or spark. Use only in well-ventilated areas. Keep away from children and animals.

**DIPOSAL:** Safeguard our environment. Dispose of container, residue and excess product in accordance with all federal, provincial and local laws and regulations.

**PACKAGING:** 325G aerosol can, packed 12 per case.

**U.P.C. CODE:** 0-60959-00448-1

**WEIGHT PER CASE:** 16 lbs. 7.27 kg

**CASE SIZE:** 11 x 8 x 8