



PRODUCT INFORMATION

PRODUCT: LIQUID RADIATOR REPAIR

PART NO.: C312C

FUNCTION AND APPLICATION: Stops leaks in radiators and prevents new leaks from developing. Works in water or anti-freeze solutions. Draining and flushing upon addition is not necessary, unless system is extremely corroded or dirty. Contains rust inhibitor. Will not harm metal, rubber hoses, gaskets, or any part of the cooling system. For use on cars, tractors or small trucks. Larger vehicles may require 2 cans.

OUTSTANDING PROPERTIES: Non-clogging, free flowing. Guaranteed to work when used as directed.

USE DIRECTIONS: Start motor with radiator nearly full and cap loose. When engine is hot, shake can thoroughly. Pour contents into radiator gradually. Run engine for a few minutes until all leaks stop. **DO NOT POUR ON A HOT CORE. Caution: Never remove pressure cap from a hot engine.** Burns may result from contents spewing over and causing injury.

PRODUCT LIMITATIONS: Will not stop major leaks or solve major mechanical problems.

PRECAUTIONS: View MSDS at [www.gunk.ca](http://www.gunk.ca)

STORAGE & HANDLING: Store away from acids. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: 325 ml in composite can with pull top lid, packed 12 per case.

U.P.C. CODE: 0-60959-02815-9

WEIGHT PER CASE: 11 lbs. 5kg

CASE SIZE: 11 X 8.25 X 5.5