



**PRODUCT INFORMATION**

**PRODUCT: HYDRAULIC JACK OIL**

**PART NO.: J132C**

**FUNCTION AND APPLICATION: For use in all hydraulic jacks, snowplows and refillable shock absorbers. Intermixes completely with all other standard hydraulic jack fluids.**

**OUTSTANDING PROPERTIES: Formulated with rust inhibitors, anti-wear agents, oxidation inhibitors and anti-foam agents.**

**USE DIRECTIONS: To keep foreign matter from entering fluid chamber, wipe fill plug and area around it before removing plug from chamber. If using aerosol container, insert snorkel into spray button on aerosol can. Place small tube into the jack's filling port. Spray oil until liquid starts to come out of the port or to the designated fill line. If using pour container, use appropriate funnel or other means of preventing spill, and follow manufacturer's recommendations for proper fill level. Keep fill at maximum level at all times. To keep hydraulic equipment in good condition, periodically drain system and refill with fresh fluid. CAUTION: DO NOT USE IN HYDRAULIC BRAKE SYSTEMS OR AUTOMATIC TRANSMISSIONS.**

**PRECAUTIONS: View MSDS at [www.gunk.ca](http://www.gunk.ca)**

**STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 50°C. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.**

**DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial, and local laws and regulations.**

**PACKAGING: J132C – 946ml plastic bottle, packed 12 per case**

**U.P.C.CODE: J132C – 0-60959-02595-0**

**WEIGHT PER CASE: J132C – 27lbs. 12.27 kg**

**CASE SIZE: J132C – 13 x 12 x 10**