



PRODUCT INFORMATION

PRODUCT: WHITE LITHIUM GREASE

PART NO.: L616C, L666, L6200

FUNCTION AND APPLICATION: Use to reduce friction in all metal-to-metal and metal-to-plastic applications. Use on hinges, locks, doorstop latches and striker plates, speedometer cables, brake cables, distributor cams, battery terminals, etc.

OUTSTANDING PROPERTIES: Reduces friction between metal to metal or metal to plastic applications. Aerosol sprays on as a liquid, and then sets up as lubricating grease that will not melt, run, wash off or freeze. Protects against rust and corrosion.

USE DIRECTIONS: Shake well before using. Spray directly on parts to be lubricated. Use tube for hard to reach applications. Use above 10°C.

PRODUCT LIMITATIONS: Use only where lithium grease is advised.

PRECAUTIONS: View MSDS at www.gunk.ca

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 50°C. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: L616C - 290g aerosol, packed 12 per case.
L666 - 454g plastic tub, packed 12 per case.
L 6200 - 200g squeeze tube, 12 per case.

U.P.C. CODE: L616C - 0-60959-12062-4,
L666 - 0-60959-01343-8,
L6200 - 0-60959-02732-9

WEIGHT PER CASE: L616C - 12 lbs. 5.45 kg L666 - 15 lbs. 6.81 kg L6200 - 6 lbs. 2.7 kg

CASE SIZE: L616C - 11 x 8 x 9. L666 - 19 x 15 x 4. L6200 - 10 x 6 x 9 1/2.