

# PRODUCT INFORMATION



## SQUEAL MEDIC™ CALIPER GREASE

CODE: L908C

PAGE

1 of 1

DATE

May 2011

**FUNCTION AND APPLICATION:** Solder Seal/Gunk® Squeal Medic™ Caliper Grease is a molybdenum disulfide fortified synthetic lubricant formulated to lubricate under the most adverse conditions. It is excellent for lubrication in high temperature applications where other greases fail.

**OUTSTANDING PROPERTIES:** Squeal Medic™ Caliper Grease has excellent corrosion resistance, a wide temperature range, and excellent extreme pressure protection. Squeal Medic™ Caliper Grease is non-melting and is water-resistant. It is excellent on all bearings and sliding surfaces in conditions above 500°F and is compatible with most rubber and plastic hardware including ethylene propylene rubber.

**USE DIRECTIONS:** Wire brush the caliper housing and anchor plate to remove all dirt and dust. Remove loose dirt from surface to be treated. Surface should be clean and dry. Apply grease to all moving caliper hardware mating surfaces and steel backing plates of the disk brake pad. Any excessive grease squeezed out from between mating surfaces must be removed. Apply sparingly.

**PRECAUTIONS:** View MSDS at [www.gunk.ca](http://www.gunk.ca)

**STORAGE & HANDLING:** Store in a cool place below 120°F away from ignition sources and oxidizing agents. Keep away from children and animals.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** 228 GRAM bottle.

## Radiator Specialty Company

CHARLOTTE, N.C./ MISSISSAUGA ON

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.