



PRODUCT INFORMATION
PRODUCT: PUNCTURE SEAL
PART NO.: M1115C, M1120C

FUNCTION AND APPLICATION: No tools! No jacks! No mess! Non-Flammable Puncture Seal safely seals and inflates tires in seconds, even while on the car! Seals punctures up to 3/16" on tube or tubeless tires. An aerosol tire inflator and sealant containing a latex sealer and a pressurizing gas utilizing R134a refrigerant. Radiator Specialty holds a patent on the use of R134a in aerosol tire inflators.

OUTSTANDING PROPERTIES: Provides a quick, safe method of repairing punctures in tires when in dark, remote or isolated areas. Can be used by anyone without tools or jacks. Contains no hydrocarbon gas or flammable solvents! Works on all types of tires, tube or tubeless, on all automotive vehicles. Completely non-flammable and contains no ozone depleters. Contents will freeze but freezing will not harm the product. Extra long shelf life. Patented propellant.

USE DIRECTIONS: 1) Shake well before using! Caution: do not use on motorcycles, bicycles or other vehicles with less than four wheels. Deflation and loss of control can result in serious injury. Not intended for use with faulty valve, sidewall or major tire damages, or if tire separates from rim. Warm can inside of car if weather is cold. Do not warm with open flame or electric heater due to possibility of can rupture. 2) If object that caused puncture is still in the tire do not remove. 3) Remove valve extension, if present. Attach filling hose by screwing firmly on the tire valve stem. Some tires may require hubcap removal. 4) Remove protective cap from top of can. Holding can in an upright position, press button to release sealant-inflator into tire. Inflate until rim is off the ground. 10 to 15 pounds of pressure is adequate. DO NOT OVERINFLATE. 5) Release button and unscrew hose from valve stem, immediately drive for 5 to 8 km to allow Puncture Seal to spread evenly and form a bond with inner surface of tire or tube. Normally, where the puncture is 3/16" or less in diameter, a Non-Flammable Puncture Seal temporary repair will get you on your way. However, the tire should be examined as soon as possible by a professional for internal damage and a permanent repair made. 6) At earliest convenience, especially before repairing tire, completely release Puncture Seal gas in a well-ventilated area. Refill with air only. Have the tire repaired by a professional as soon as possible.

PRODUCT LIMITATIONS: Should not be considered a permanent repair. Puncture holes made by an object larger than 3/16"(5mm) may not be plugged adequately. DO NOT USE PUNCTURE SEAL IN COMBINATION WITH ANY OTHER TYPE OR BRAND OF TIRE INFLATOR. MIXING WITH OTHER SIMILAR PRODUCTS COULD CAUSE TIRE FAILURE OR CREATE AN EXPLOSION HAZARD. For larger tire sizes, use M1128 JUMBO size can.

PRECAUTIONS: Inhaling concentrated vapors, intentionally or otherwise, can cause death without warning. In case of inhalation, move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance. If eye contacted, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. For skin contact, wash with soap and water. If swallowed, drink water. Induce vomiting and seek immediate medical assistance.

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not store in the passenger compartment of a car or in the exposed storage area of a hatch back. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 50°C. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: M1115C – 510g aerosol, 6 per case
M1120C – 680g aerosol, 6 per case

U.P.C. CODE M1115C - 0-60959-02987-3 M1120C - 0-60959-02988-0

WEIGHT PER CASE: M1115C – 10 lbs. 4.5 kg M1120C – 11.8 lbs 5.4 kg