

PRODUCT INFORMATION



SYNTHETIC MOTOR FLUSH FOR TURBO-CHARGED DIESEL AND GAS ENGINES.

Code: MFD2C

Page: 1 of 1

Date: May 2011

FUNCTION AND APPLICATION: A unique blend of synthetic solvents that effectively removes gum, varnish, and sludge deposits and frees sticking valves and rings safely on turbo-charged diesel and gasoline engines.

OUTSTANDING PROPERTIES: An inexpensive way to clean up the internal components of an engine. Is safe for use on all diesel and gas engines and cleans in 5 minutes. Can be easily used by car owners or professional technicians just before oil changes,

USE DIRECTIONS: 1. Check that engine oil is at a safe operating level. 2. Add MFD1 to cold engine before changing oil and filter. Idle-engine at normal speed for 5 minutes to allow the product to circulate throughout the entire lubricating system of your engine. **DO NOT DRIVE THE CAR.** 3. Drain oil and remove old oil filter. 4. Replace filter and drain plug and refill engine with new oil.

NOTE: On engines with high mileage or excessive deposits repeat steps 1 through 4. **IMPORTANT:** Use entire contents of container after opening. Do not store partially used container.

PRECAUTIONS: View MSDS at www.gunk.ca.

STORAGE & HANDLING: Store in a cool place below 120⁰F away from acids, ignition sources and oxidizing agents. Keep away from children and animals.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: Packaged in 946 ml plastic bottle.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.