



PRODUCT INFORMATION

PRODUCT: LIGHT CUTTING OIL

PART NO.: SUL2C, SUL3C

FUNCTION AND APPLICATION: Solder Seal Light Cutting Oil is formulated for hand threading applications.

OUTSTANDING PROPERTIES: Solder Seal Light Cutting Oil is a high grade sulfured-chlorinated base oil that helps cut clean, sharp threads on steel and brass pipes. Helps dissipate heat, prevents tool lock up, prevents heat build up, and helps retard corrosion on newly threaded parts. Also helps prevent the chips from welding to the edge of the cutting tool. For high-speed machines use Solder Seal Dark Cutting Oil.

USE DIRECTIONS: Apply the Solder Seal Light Cutting Oil with a squirt can. Apply the oil before tool is in contact with pipe. Oil should be applied to the point of friction for best results.

PRECAUTIONS: View MSDS at www.gunk.ca.

STORAGE & HANDLING: Store in a cool place below 50°C away from acids, ignition sources and oxidizing agents. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: SUL2C – 946ml plastic bottle packed 12 per case
SUL3C – 3.78L plastic bottle packed 4 per case

U.P.C. CODE: SUL2C – 0-60959-02881-4
SUL3C – 0-60959-02883-8

M.S.D.S.: MS-SUL

WEIGHT PER CASE: SUL2C – 27lbs 12.2 kg SUL3C – 34lbs 15.4 kg

CASE SIZE: SUL2C – 14 ½ x 11 X 8
SUL3C – 14 x 10 x 12