



PRODUCT INFORMATION

PRODUCT: TITSEAL UNDERCOATING

PART NO.: T1617RC

FUNCTION AND APPLICATION: An aerosol undercoating designed to protect car body from rust and corrosion. Useful after do-it-yourself repairs and replacement of parts. Protects against moisture, dirt, corrosive road salt and improves auto body soundproofing.

OUTSTANDING PROPERTIES: A low cost product that requires no special tools or skills to apply. One can may be used for many different applications. T1617R rubberized version remains flexible and may be painted.

USE DIRECTIONS: Shake can until agitator ball moves freely. Surface to be sprayed should be clean and dry. Contents should be at room temperature. Hold can at 12 inches from surface to be sprayed. Apply a uniform coating. After use, clean nozzle by inverting can and spraying a short burst.

PRODUCT LIMITATIONS: This product is not intended to be a replacement for OEM or professional undercoating. If overspray occurs, use Gunk Tar & Bug Remover for easy removal. Do not spray on catalytic converter.

PRECAUTIONS: View MSDS at www.gunk.ca.

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 50°C. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Do not spray on or close to exhaust systems or catalytic converters. Use with adequate ventilation. Avoid contact with skin or eyes. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: T1617R C- 454G aerosol tin, packed 12 per case.

U.P.C. CODE:T1617RC - 0-60959-20162-0

WEIGHT PER CASE: T1617RC- 17 lbs. 7.7 kg

CASE SIZE: T1617RC - 11 x 9 x 10