



PRODUCT INFORMATION

PRODUCT: TITE-SEAL® GASKET & JOINT SEALING COMPOUND LIGHT WEIGHT

PART NO.: T2066, T2075

FUNCTION AND APPLICATION: TITE-SEAL® LIGHT WEIGHT is a flexible compound for use as a joint sealing compound, caulking compound, corrosion preventative, lubricant, threaded joint dressing insulating material or filler with packing. Used on head and manifold gaskets of automotive and aircraft engines, water heater fittings and gaskets, gas range valves and fittings, pipe threads on dry-cleaning solvent filters, railroad and truck air-brakes, fittings and lines, etc. For all metal-to-metal unions with any kind of gasket.

OUTSTANDING PROPERTIES: TITE-SEAL® LIGHT WEIGHT is unaffected by water, oil, gasoline, glycerin, steam, gas vapor, exhaust fumes and most hard-to-hold liquids. Withstands extreme temperatures; will not harden, making connections, vibration-proof and easy to disassemble for repairs and adjustments. Prevents corrosion and "freezing" of metal parts. Expands and contracts with temperature changes without affecting seal.

USE DIRECTIONS: TITE-SEAL® LIGHT WEIGHT will form seals at temperature ranges of -5°C to 120°C. Before applying wipe surfaces dry and clean. Then simply spread on. With gaskets: Coat joint surfaces, spreading evenly. Without gaskets: Coat joint surfaces and embed small thread or string as binder. As a filler: Apply as a bond between regular packing and metal surfaces. Do not use thinner.

PRECAUTIONS: May be skin and eye irritant to sensitive persons. Harmful if swallowed. In case of contact, wash skin with soap and water. For eye contact, flush promptly with water for at least 15 minutes. If ingested, drink 2 glasses of milk; do not induce vomiting. Call a physician immediately.

STORAGE & HANDLING: Store in a cool place below 50°C away from acids, ignition sources and oxidizing agents. Keep lid tightly closed. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: T2066 – 1lb. metal tin T2075 – 5lb. metal tin

U.P.C. CODE: T2066 – 0-60959-02134-1 T2075 – 0-60959-02135-8

WEIGHT PER CASE: T2066 – 17lbs. 7.72 kg T2075 – 33lbs. 15 kg

CASE SIZE: T2066 – 14 x 10 x 5 T2075 – 20 x 13 ½ x 5