



PRODUCT INFORMATION

PRODUCT: TITE-SEAL® GASKET & JOINT SEALING COMPOUND MEDIUM WEIGHT

PART NO.: T2566, T2575

FUNCTION AND APPLICATION: Seals with gasket...or as a gasket. Seals pumps, tanks, pressed plates, covers, pans, etc., for pipe threads and imperfect or uneven surfaces. For general gasketing and machine joints, cylinder heads, manifolds, differentials, transmissions, and muffler joints. For sealing radiator hose connections... as a filler for water pump packing. Used as a gasket for gear housing that must retain oil and grease on appliances of all types.

OUTSTANDING PROPERTIES: TITE-SEAL® GASKET & JOINT SEALING COMPOUND is heatproof, vibration-proof, non-solvent, non-shrinking, non-crumbling, non-cracking. Prevents rust, corrosion and seizure of joints, bolts, and nuts, studs and threaded fittings. It withstands high temperatures and pressures, the actions of water, gasoline, kerosene, grease, oil, L-P and natural gas, steam, hot or cold water, glycerin, ethylene glycol, ammonia, etc.

USE DIRECTIONS: Before applying wipe surfaces dry and clean. Then simply spread on. With gaskets: coat joint surfaces, spreading evenly. Without gaskets: coat joint surfaces and embed small thread or string as a binder. As a filler: apply as a bond between regular packing and metal surfaces. Do not use thinner.

PRECAUTIONS: Contains a mixture of vegetable oils. May be skin and eye irritant to sensitive persons. Harmful if swallowed. In case of eye contact flush with water for at least 15 minutes. For skin contact, wash with soap and water. If ingested, drink 2 glasses of milk: do not induce vomiting. Call a physician immediately.

STORAGE & HANDLING: Store in a cool place below 50°C away from acids, ignition sources and oxidizing agents. Keep lid tightly closed when not in use. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

DISPOSAL: Safeguard our environment. Dispose of container, residue, and excess product in accordance with all federal, provincial and local laws and regulations.

PACKAGING: T2566 – 1lb. metal tin T2575 – 5lb metal tin

U.P.C. CODE: T2566 – 0-60959-02137-2 T2575 – 0-60959-02138-9

WEIGHT PER CASE: T2566 – 17lbs. 7.7 kg T2575 – 33lbs. 15 kg

CASE SIZE: T2566 – 14 x 10 x 5 T2575 – 20 x 13 ½ x 5